Cerenkov performance limits due to phototube – base combination

David Christian May 13, 2014

Phototube – Base

- We use an ET 9215B 8-stage phototube and an ET "fully transistorized" base (voltage divider).
- ET reprint says, "photomultipliers should not be operated for any length of time at anode currents in excess of 100 μ A..."
- QIE least count \approx 3.2 fC. Operating at 53.1 MHz, this is 3.2fC/18.8ns = 0.17 μ A.
 - \rightarrow 100 μA ≈ 600 QIE units.

Average current at 5E12

- During 4 turn injection run recently, G2SEM was ~5.2E12 protons per pulse.
- With phototube HV = 870V, QIEsum was ~1.2E11/spill (after subtracting pedestal of ~. 07E11)
- Ave QIE value ~ 1.2E11/207E6 = 580.
- Close to, but under the recommended maximum current.

Pulse performance – deviation from linearity (10 μs pulse)

- 700V curve deviates at ~2.5 mA.
- 700V curve is 5% low at 10 mA.
- 900V curve deviates at slightly higher current.
- 900V curve is 5% low at ~15mA.
- 900V curve is 10% low at ~20mA.




figure 5 linearity performance for pulses of width 1 μ s. The deviation from linear amplification is a limitation of the pmt, and not to the divider.

Comparison to our data

- 700V curve deviates at ~2.5 mA.
- 700V curve is 5% low at 10 mA.
- 900V curve deviates at slightly higher current.
- 900V curve is 5% low at ~15mA.
- 900V curve is 10% low at ~20mA.

- 2.5 mA = 14700 QIE
- 15 mA = 88000 QIE
- 20 mA = 118000 (just above high end of range)
- Maximum observed during recent high intensity run ~ 60,000 – 80,000.

What does it mean?

- The current running condition is not too bad.
- QIESum/G2SEM ratio implies ~2% sag at 5E12.
- Don't know whether loss comes in:
 - Single buckets (18.8ns time scale)
 - Few high buckets
 - Single Booster batch (1.5 μ s)
 - Single turn (11 μ s)
 - Multiple turns